

e^N-Check 2500 SP

The new standard in check readers



Continuing the tradition of providing the highest performance check readers in the industry, Ingenco designed the e^N-Check 2500 SP with an array of features. The 2500 SP comes equipped with the ability to read Secure Product's stealth mark printed on select customer checks. Ergonomic modifications enhance its appearance and improve its read rate. The compact size and installation options allow it to be placed virtually anywhere. The 2500 SP has a intuitive check staging area and increased processing speed making it the check reader of choice for improving customer service and reducing fraud. And it's brought to you by the company with more check readers installed worldwide than anyone, Ingenco.



World leader in secure financial transaction solutions

e^N-Check 2500 SP

The new standard in check readers

Quiet, efficient, and accurate. Three words that describe the most versatile check reader on the market today. Ingenico has used the experience we gained in becoming the global leader in check reading technology to bring you the e^N-Check 2500 SP.

Expressly Created for Superior Security

- ¥ 2500 SPreads MICR line to verify format and ABA number
- ¥ 2500 SPdetects presence or absence of Secure Products stealth mark
- ¥ If stealth mark is not read, 2500 SPholds back check and displays an exception code on its LCD and/or sends an error message to the teller PC

Ergonomically Designed for Flexibility & Simplicity

- ¥ The angle of the check entry area and intuitive design enhance ease-of-use
- ¥ Enhanced cable channeling allows the combined power/communications cable to be routed out the back or side of the e^N-Check 2500 SP

Expressly Created for Optimal Performance

- ¥ Improved recognition algorithms produce highly-accurate, first-pass reads
- ¥ 7-segment display provides detailed bad check information
- ¥ Rapid read times enhance customer service

Specifically Built to Protect Your Investment

- ¥ Modular design allows users to add options such as check trays for sorting, image capture devices, and interface to PCs hosts
- ¥ Automatically detects communication interfaces on power up
- ¥ Users can implement check conversion with or without the addition of image capture devices

TECHNICAL CHARACTERISTICS



| | |
|------------------------|---|
| MICR Fonts | G3B ONE, and ONE |
| Magnetic Stripe Reader | Optional - dual or triple track, bi-directional |
| Average Track Speed | 21 inches per second (533 mm per second) |
| User Display | 7 segment readout and LCD with 3 colors |
| Application Software | Reloaded |
| Programmability | Downloadable via platform, configuration checks or PC Field upgradeable firmware via flash ROM |
| Interfaces | IBM MICR Fujitsu/SEL Symbol Tech., VisaTone, Hypercom and most other POS PC, wedge and terminal platforms |
| Protocols | RS32, RS85, TEL Keyboard Wedge, CCA, CCA MS and others |
| Life Expectancy | One million reads |
| Voltage | 4.9 VDC to 16 VDC (maximum, including ripple) |
| Current | 400 mA normal operations (average) 250 mA quiescent |
| External Power Supply | None required in most installations when at least 300 mA is available from the PC port |
| Dimensions & Weight | 2.78" (70.6 mm) x 3.0" (76.2 mm) x 7.18" (182.4 mm) 13.4 oz (3.8 kg) |



The smallest footprint in the industry preserves counter space, allowing it to be placed in a variety of positions.



Over 400 parsing algorithms ensure the highest read accuracy in the market.

Ingenico Inc.
1003 Mansell Road - Atlanta, GA 30076
Tel: (770) 594-6000 - Fax: (770) 594-6003
www.ingenico-us.com

Ingenico Canada Ltd.
79 Barbairie Road - Toronto, Ontario
Canada M5L 1G7
Tel: (416) 245-6700 - Fax: (416) 245-6701
www.ingenico-ca.com